

## Hauteur de 6 à 12 mètres

6 to 12 meters height



Fût octo-conique en acier. 62 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.

Octagonal conical steel pole. 62 mm top dia, 2 rows of threaded holes at 100 and 200 mm from top.



### Dimensions

| HS<br>m | Øa<br>mm | Øb<br>mm | Lp<br>mm | Pp<br>mm | Hp<br>mm | Cxd<br>mm | E<br>mm | TS<br>mm    |
|---------|----------|----------|----------|----------|----------|-----------|---------|-------------|
| 6       | 62       | 190      | 600      | 130      | 500      | 110x116   | 300     | J 20/18x400 |
| 7       | 62       | 190      | 600      | 130      | 500      | 110x120   | 300     | J 20/18x400 |
| 8       | 62       | 190      | 600      | 130      | 500      | 110x124   | 300     | J 20/18x400 |
| 9       | 62       | 190      | 600      | 130      | 500      | 110x126   | 300     | J 20/18x400 |
| 10      | 62       | 190      | 600      | 130      | 500      | 110x128   | 300     | J 20/18x400 |
| 12      | 62       | 190      | 600      | 130      | 500      | 110x130   | 300     | J 20/18x400 |

### Capacités

| HS<br>m | Kg | 22 m/s |       | 24 m/s |       | 26 m/s |       | 28 m/s |       | 34 m/s |       | M     | T   | Lm x Hm<br>m |
|---------|----|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|-------|-----|--------------|
|         |    | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | m.daN | daN |              |
| 6       | 50 | 2,34   | 1,88  | 1,93   | 1,54  | 1,59   | 1,27  | 1,34   | 1,06  | 0,83   | 0,64  | 1369  | 333 | 0.6x1.0      |
| 7       | 50 | 1,78   | 1,44  | 1,44   | 1,16  | 1,20   | 0,94  | 0,99   | 0,76  | 0,57   | 0,42  | 1415  | 330 | 0.6x1.0      |
| 8       | 50 | 1,37   | 1,09  | 1,10   | 0,85  | 0,88   | 0,67  | 0,70   | 0,52  | 0,35   | 0,23  | 1440  | 333 | 0.6x1.0      |
| 9       | 50 | 1,04   | 0,79  | 0,79   | 0,60  | 0,61   | 0,44  | 0,46   | 0,32  | 0,17   | 0,07  | 1453  | 323 | 0.6x1.0      |
| 10      | 50 | 0,76   | 0,56  | 0,56   | 0,39  | 0,40   | 0,25  | 0,27   | 0,15  | -      | -     | 1451  | 294 | 0.6x1.0      |
| 12      | 50 | 0,82   | 0,60  | 0,59   | 0,40  | 0,41   | 0,25  | 0,27   | 0,13  | -      | -     | 2167  | 347 | 0.6x1.2      |

Accessoires et options  
PORTE



SAUF 12 M

Accessoires et options  
PIED DE MÂT

