

Hauteur de 3 à 6 mètres  
3 to 6 meters height



Fût rond-conique en acier, 60 mm en tête pour lanterne en top uniquement.  
Trou Ø 12 à 70 mm du sommet.

Round-conical steel pole, 60 mm for lantern at top only. One hole of Ø 12mm dia at 70 mm from top.




### Dimensions

HS m	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	Cxd mm	E mm	TS mm
3	60	102	450	72	500	54x60	200	J 16/14x300
3,5	60	109	450	72	500	55x69	200	J 16/14x300
4	60	116	450	80	500	70x60	200	J 16/14x300
4,5	60	123	450	80	500	70x70	200	J 16/14x300
5	60	130	500	85	500	78x72	200	J 16/14x300
6	60	144	500	85	500	78x90	200	J 16/14x300

### Capacités

HS m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M m.daN	T daN	Hm Lm x Hm m
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I			
3	30	0,93	0,79	0,76	0,65	0,64	0,54	0,54	0,45	0,34	0,28	231	98	0.5x0.5
3,5	30	0,90	0,75	0,75	0,60	0,61	0,49	0,51	0,42	0,31	0,25	275	103	0.5x0.5
4	30	0,76	0,60	0,61	0,48	0,51	0,39	0,42	0,32	0,25	0,19	289	101	0.5x0.5
4,5	30	0,73	0,57	0,59	0,46	0,48	0,37	0,39	0,30	0,23	0,17	337	107	0.5x0.5
5	30	0,60	0,47	0,48	0,37	0,39	0,29	0,31	0,23	0,17	0,12	350	105	0.5x0.6
6	30	0,55	0,42	0,42	0,32	0,33	0,24	0,26	0,19	0,13	0,09	444	116	0.5x0.7

Accessoires et options  
PORTE



Accessoires et options  
PIED DE MÂT

