

OMEGA 89

Hauteur de 4 à 12 mètres
4 to 12 meters height



Fût rond-conique en acier. 89 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.

Round-conical steel pole. 89 mm top dia, 2 rows of threaded holes at 100 and 200 mm from top.



Dimensions

HS m	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	Cxd mm	E mm	TS mm
4	89	151	450	85	500	85x96	200	J 16/14x300
5	89	167	500	91	500	90x110	300	J 20/18x400
6	89	180	500	100	500	95x125	300	J 20/18x400
7	89	198	500	102	500	95x145	300	J 20/18x400
8	89	226	500	103	500	100x170	300	J 20/18x400
9	89	243	500	104	500	100x185	300	J 20/18x400
10	89	267	500	105	500	100x215	300	J 20/18x400
12	89	256	600	140	500	135x195	300	J 20/18x400

Capacités

HS m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M m.daN	T daN	Lm x Hm m
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I			
4	50	2,49	2,00	2,10	1,66	1,76	1,39	1,51	1,20	1,00	0,79	764	216	0.5x0.8
5	50	2,08	1,66	1,71	1,37	1,44	1,16	1,22	0,99	0,81	0,65	903	216	0.6x0.8
6	50	1,71	1,37	1,39	1,14	1,18	0,95	1,00	0,81	0,65	0,53	1019	217	0.6x0.8
7	50	1,66	1,34	1,37	1,11	1,14	0,93	0,96	0,78	0,62	0,50	1256	242	0.6x0.9
8	50	1,83	1,49	1,51	1,25	1,27	1,04	1,07	0,88	0,68	0,55	1667	291	0.6x1.1
9	50	1,76	1,47	1,44	1,20	1,22	1,00	1,03	0,84	0,64	0,51	1945	319	0.6x1.2
10	50	1,83	1,54	1,51	1,25	1,27	1,04	1,06	0,87	0,65	0,51	2344	362	0.6x1.3
12	50	1,44	1,20	1,17	0,96	0,96	0,78	0,79	0,64	0,44	0,32	2589	375	0.6x1.4


BON À SAVOIR

Se reporter à la gamme accessoires/embouts démontables pour prévoir la liaison fût/luminaire.

TIP

For connections to lantern see accessories range/removable spigots.

Accessoires et options
PORTE



Accessoires et options
PIED DE MÂT

