



# ORANE 76

Hauteur de 3 à 6 mètres  
3 to 6 meters height

ACIER  
STEEL

Fût rond-conique en acier. 76 mm en tête, avec embout soudé Ø 60x70mm

Round-conical steel pole, 76mm top dia with a welded spigot dia 60x70mm on top



## Dimensions

HS m	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	Cxd mm	E mm	J TS mm
3	76	118	450	72	500	65x65	200	J 16/14x300
3,5	76	125	450	73	500	65x70	200	J 16/14x300
4	76	132	450	74	500	70x75	200	J 16/14x300
4,5	76	139	500	87	500	80x75	200	J 16/14x300
5	76	146	500	88	500	80x85	200	J 16/14x300
5,5	76	159.4	500	90	500	85x95	300	J 20/18x400
6	76	167	500	102	500	95x100	300	J 20/18x400

## Capacités

HS m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M m.daN	T daN	Lm <sup>2</sup> Lm x Hm m
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I			
3	50	2,05	1,76	1,71	1,47	1,44	1,22	1,22	1,05	0,80	0,70	461	173	0.5x0.6
3,5	50	1,93	1,59	1,61	1,32	1,34	1,11	1,14	0,94	0,75	0,61	520	171	0.5x0.6
4	50	1,86	1,47	1,51	1,21	1,27	1,01	1,09	0,85	0,71	0,56	595	174	0.5x0.6
4,5	50	1,47	1,16	1,21	0,95	1,00	0,79	0,84	0,67	0,54	0,43	585	158	0.5x0.6
5	50	1,39	1,10	1,14	0,90	0,94	0,75	0,79	0,62	0,51	0,40	655	163	0.5x0.7
5,5	50	1,49	1,18	1,22	0,98	1,01	0,80	0,85	0,68	0,55	0,44	800	181	0.6x0.7
6	50	1,27	1,01	1,03	0,83	0,85	0,68	0,72	0,58	0,46	0,37	820	177	0.6x0.7

Accessoires et options  
PORTE



Accessoires et options  
PIED DE MÂT



**BON À SAVOIR**  
Fixation directe  
de la lanterne

**TIP**  
Direct mounting  
of the luminaire