

STYLE

Hauteur de 3,5 à 6 mètres
3,5 to 6 meters height



Fût octo-conique en acier. 60 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.

Octagonal conical steel pole, 60 mm top dia, 2 rows of threaded holes at 100 and 200 mm from top.



Dimensions

HS m	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	Cxd mm	E mm	TS mm
3,5	60	156	500	95	600	75x90	200	J 16/14x300
4	60	156	500	95	600	80x90	200	J 16/14x300
4,5	60	156	500	95	600	80x95	200	J 16/14x300
5	60	156	500	95	600	80x100	200	J 16/14x300
6	60	156	500	95	600	80x105	200	J 16/14x300

Capacités

HS m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M	T	Hm
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	Lm x Hm m
3,5	50	2,64	2,17	2,20	1,81	1,86	1,51	1,59	1,29	1,04	0,84	707	251	0.5x0.7
4	50	2,27	1,81	1,88	1,49	1,59	1,25	1,34	1,06	0,87	0,67	736	241	0.5x0.8
4,5	50	1,90	1,51	1,56	1,25	1,32	1,04	1,11	0,87	0,68	0,53	744	231	0.5x0.8
5	50	1,59	1,27	1,29	1,04	1,09	0,84	0,90	0,70	0,54	0,41	758	227	0.5x0.8
6	50	1,12	0,88	0,89	0,70	0,72	0,56	0,59	0,44	0,31	0,22	779	226	0.5x0.8

BON À SAVOIR

Le STYLE équipé d'un embout fileté (sur demande) est très utilisé avec un luminaire de style en top.

TIP

The Style, which comes equipped with an inner-threaded end-piece (on demand) is often used with a style lantern on top.

Accessoires et options
PORTE



Accessoires et options
PIED DE MÂT

