



TRAFIC


Saillie de 3,5 à 5,5 mètres
3,5 to 5,5 meters outreach

Potence en aluminium. Fût et crosse rond-conique emboîtés.
Hauteur totale de 7,10 m.


Aluminium cantilever. Round-conical shaft and slip jointed bracket. 7.10 total meters height.



Dimensions

 S m	 Øa mm	 Øb mm	 Lp mm	 Pp mm	 Hp mm	 cxd mm	 E mm	 TS mm
3,5	106	225	400	85	600	85x170	300	J 25/24x600
4	100	225	400	85	600	85x170	300	J 25/24x600
4,5	100	225	400	85	600	85x170	300	J 25/24x600
5,5	101	225	400	85	600	85x155	300	J 25/24x600

Capacités

 S m	 Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M	T	 Lm x Hm m
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
3,5	50	2,12	1,76	1,76	1,44	1,49	1,22	1,27	1,03	0,81	0,64	1842	315	0.6x1.1
4	50	1,78	1,47	1,47	1,21	1,22	1,00	1,05	0,84	0,66	0,52	1737	298	0.6x1.1
4,5	50	1,49	1,21	1,22	0,99	1,01	0,82	0,85	0,68	0,53	0,41	1659	285	0.6x1.0
1 feu 1 spotlight														
5,5	50	1,86	1,51	1,54	1,25	1,27	1,04	1,09	0,87	0,66	0,51	2197	359	0.6x1.2
1 feu intermédiaire à 2,8 m puis un feu à l'extrémité à 5,5 m A middle course stoplight at 2,8 meters and a top stoplight at 5.5 meters														
5,5	35	1,16	0,94	0,95	0,77	0,79	0,65	0,67	0,54	0,42	0,32	2405	393	0.6x1.2

Accessoires et options
PORTE



Accessoires et options
PIED DE MÂT



AUTRES APPLICATIONS
OTHER APPLICATIONS MATS