



# VENUS 2

Hauteur de 4 à 6 mètres  
4 to 6 meters height

Fût rond-conique en aluminium. 60 mm en tête.

Round-conical aluminium pole, 60 mm top dia.



## Dimensions

| HS<br>m | Øa<br>mm | Øb<br>mm | Lp<br>mm | Pp<br>mm | Hp<br>mm | cxd<br>mm | E<br>mm | J<br>TS<br>mm |
|---------|----------|----------|----------|----------|----------|-----------|---------|---------------|
| 4       | 60       | 150      | 600      | 95       | 500      | 95x85     | 200     | J 16/14x300   |
| 5       | 60       | 150      | 600      | 95       | 500      | 95x85     | 200     | J 16/14x300   |
| 6       | 60       | 150      | 500      | 95       | 500      | 95x85     | 200     | J 16/14x300   |

## Capacités

| HS<br>m | Kg | 22 m/s |       | 24 m/s |       | 26 m/s |       | 28 m/s |       | 34 m/s |       | M<br>m.daN | T<br>daN | Lm x Hm<br>m |
|---------|----|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|------------|----------|--------------|
|         |    | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I |            |          |              |
| 4       | 40 | 1,34   | 1,06  | 1,11   | 0,87  | 0,93   | 0,72  | 0,78   | 0,61  | 0,50   | 0,39  | 449        | 132      | 0.5x0.6      |
| 5       | 40 | 0,84   | 0,66  | 0,67   | 0,53  | 0,56   | 0,43  | 0,46   | 0,35  | 0,28   | 0,21  | 450        | 117      | 0.5x0.6      |
| 6       | 40 | 0,52   | 0,39  | 0,40   | 0,30  | 0,31   | 0,23  | 0,24   | 0,18  | 0,12   | 0,09  | 450        | 111      | 0.5x0.6      |



ALUMINIUM  
ALUMINIUM

Accessoires et options  
PORTE



Accessoires et options  
PIED DE MÂT

