

FIXED EQUIPMENT CIRCULAR PLATFORMS

DESCRIPTION | DECISIVE ADVANTAGES



Circular platform is particularly suited to a 360° lighting of wide outdoor spaces. Platform is mounted on high mast top.

The center octogonal maintenance platform can holp up 2 persons for floodlights maintenance operations. This maintenance platform is also spacious (2.68m²) and secure, in compliance with standards.

A $\emptyset 2.4 m$ ring around the platform allows to mount up to 20 sitting and hanging floodlights.



TECHNICAL DESCRIPTION



- Bolted on an welded plate at the top of the mast
- Suitable for masts with top diameter between 160 and 310 mm
- A central stem on the maintenance platform allows safety cable securing.
- Electrical cables come out of the mast under the platform by 1 or 2 Ø101 mm steel tubes.



- 1 1675 mm wide non-slipping floor
- 2 platform access hatch
- 3 floodlights fixing ring
- 4 railing posts
- 5 central stem for safety cable

Lighting configurations:

- Single-side lighting
- Two-sides lighting
- Circular lighting



PFC15/12 with 5 hanging floodlights on a single-side



PFC15/12 with 5 sitting and 5 hanging floodlights on a single-side



PFC15/12 with 6 sitting and 6 hanging floodlights on two sides.



PFC15/12 with 10 sitting floodlights 360° arrangement



PFC15/12 with 10 sitting and 10 hanging floodlights - 360° arrangement

COMPLIANCE

Our platforms are in compliance with NFE 85014 standards (industrial equipment elements, work platforms).