


TCA

Hauteur de 3 à 5 mètres
3 to 5 meters height



ALUMINIUM
ALUMINIUM



Fût cylindrique en aluminium. Diamètre 90 ou 120 mm.


Cylinder-shaped aluminium pole. 90 or 120 mm diameter.



Dimensions

								
HS mm	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	cxd mm	E mm	TS mm
TCA 90								
3	90	90	400	60	500	55x55	200	J 16/14x300
3,5	90	90	400	60	500	55x55	200	J 16/14x300
4	90	90	400	60	500	55x55	200	J 16/14x300
4,5	90	90	400	60	500	55x55	200	J 16/14x300
5	90	90	400	60	500	55x55	200	J 16/14x300
TCA 120								
3,5	120	120	460	85	500	70x82	200	J 16/14x300
4	120	120	460	85	500	70x82	200	J 16/14x300
4,5	120	120	460	85	500	70x82	200	J 16/14x300
5	120	120	460	85	500	70x82	200	J 16/14x300

Capacités

		22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M	T	
HS m		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	Lm x Hm m
TCA 90														
3	40	1,11	0,95	0,92	0,78	0,76	0,65	0,65	0,55	0,42	0,35	286	112	0.5x0.5
3,5	40	0,83	0,67	0,67	0,54	0,56	0,45	0,46	0,37	0,29	0,24	278	100	0.5x0.5
4	40	0,62	0,48	0,49	0,38	0,40	0,31	0,33	0,25	0,19	0,15	276	93	0.5x0.5
4,5	40	0,45	0,34	0,34	0,26	0,27	0,20	0,21	0,16	0,11	0,08	274	90	0.5x0.5
5	40	0,31	0,22	0,23	0,16	0,17	0,11	0,12	0,08	0,05	0,03	274	88	0.5x0.5
TCA 120														
3,5	40	1,21	0,99	0,99	0,82	0,83	0,68	0,71	0,59	0,47	0,39	363	124	0.5x0.5
4	40	0,93	0,73	0,76	0,60	0,64	0,50	0,54	0,42	0,35	0,28	355	112	0.5x0.5
4,5	40	0,70	0,54	0,56	0,44	0,46	0,36	0,39	0,31	0,25	0,20	354	106	0.5x0.5
5	40	0,51	0,40	0,41	0,31	0,33	0,25	0,27	0,21	0,17	0,14	351	101	0.5x0.5

BON À SAVOIR

Adaptation sur demande :
embout soudé lisse, fileté
ou taraudé.

TIP

Adaptation upon request:
smooth, threaded or tapped
welded spigot.

Accessoires et options
PIED DE MÂT

